

DIMENSION					
PIPE SIZE	Α	В	MANDREL O.D.	PIPE O.D.	WALL THINNESS
6" SDR 26	3.5"	5.0"	5.503"	6.275"	0.214"
8" SDR 26	4.5"	6.0"	7.366"	8.400"	0.323"
10" SDR 26	5.5"	7.5"	9.207"	10.500"	0.404"
12" SDR 26	7.0"	9.0"	10.961"	12.500"	0.481"
15" SDR 26	9.0"	11.5"	13.418"	15.300"	0.588"

NOTES:

- 1. AFTER WELDING IS COMPLETED, TRUE THE OUTSIDE DIAMETER DIMENSION. FOR THE FULL LENGTH OF "B" TO 0.010".
- 2. MANDREL OD MUST BE EQUAL TO 95% OF THE ID OF THE PIPE
- 3. ADJUSTABLE MANDREL NOT ACCEPTABLE.
- 4. REFERENCE THE PIPE MANUFACTURER'S SPECIFICATIONS FOR MANDREL SIZE AND SUPPLY CALCULATED DIMENSIONS IN A SUBMITTAL.
- 5. A PROVING RING IS REQUIRED.
- 6. MANDREL WILL HAVE AN ODD NUMBER OF RUNNERS (9 OR MORE).

The City of San Marcos Engineering and Capital Improvements	1/1/2021	FIFL WANDINEL
RECORDED COPY SIGNED BY	2-15-2015	THE ARCHITECT/ENGINEER ASSUMES 5105-PM-SM RESPONSIBILITY FOR APPROPRIATE
LAURIE MOYER, P.E.	ADOPTED	USE OF THIS STANDARD N.T.S. STANDARD DETAIL